



# Hongkong Tiffany Tape Co.,Ltd

Address: No.1210 Room, No.658, Guangfulin Road, Songjiang District, Shanghai

Fax: 0086-21-6111 4576

Post Code : 201620

Whatsapp: +0086 158 5277 1138

Email: [tiffany@tiffanytape.com](mailto:tiffany@tiffanytape.com)

## PRODUCT INFORMATION

Sort:	Crepe Paper Masking Tape	Type:	TF-MG02
Constructure:	surface activator/ crepe paper/ solvent rubber adhesive		
Item	Unit	Data	Test Standard
Total thickness	μ m	140±10	GB/T 7125-1999
Initial tack (Ball test)	Ball No.	≥9#	GB/T 4852-2002
180°peel adhesion ( to stainless steel )	kN/m	≥0. 24	GB/T 2792-1998
	N/25mm	≥6. 0	
Holding power (to stainless steel)	h	≥2. 5	GB/T 4851-1998
Tensile strength	kN/m	≥2. 4	GB/T 7753-1987
	N/cm	≥24	
Elongation at break	%	≤20	GB/T 7753-1987
Temperature resistance			
<b>Applications:</b> In-door paint masking, Light duty packaging, bundling, holding, splicing & Tabbings, and other non-critical Applications where a pressure-sensitive tape is needed. <b>Color:</b> Natural white, Beige, Yellow			
<b>Product Sizes:</b> (1) Jumbo roll size: 1270mm(usable:1250mm)×1700m, 1515mm(usable:1490mm ) x 1700m (2) Cut size: As per customer requirements			
<b>Storage and Usage Conditions:</b>  1. Tape should be stored in a cool ( 20 °C ~ 30 °C ), dry ( 50% ~ 70% Humidity) area away from direct sunlight, air conditioner and other heat sources. 2. Tape jumbos should be placed vertically in well package and avoid to be pressed against glue surface. 3. Tape should be used within 12 months from date of production. Surfaces to which tape is applied should be clean, dry and free of grease, oil, moisture, dirt and other contaminants.			
<b>Remarks:</b> A. The physical and performance characteristics shown above are obtained from tests recommended by GB standard and Smith Company's Research & Development Department and do not represent a guarantee of product performance. B. Individual rolls may vary slightly from the above values. The user should try use and determine whether the product is suitable for his particular applications. There is no warranty of fitness for a particular purpose. C. We reserve the right to make changes without notice or obligation in our products and publications. D. It is always recommended for customer to trial use for their specific applications before large			
Issuance date: 2015-07-30		Version: B/0	