



香港蒂梵尼胶带有限公司

Hongkong Tiffany Tape Co.,Ltd

PRODUCT INFORMATION

SORT: PVC TAPE

TYPE: TFJ150

CONSTRUCTION

RELEASE

CARRIER:PVC FILM

Adhesive:Natural Rubber

Following data just for reference. the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes.

Item	Unit	Data	Test Standard
Total Thickness	μm	150 ± 10	ASTM D-1000
Initial tack (Ball test)	Ball no	≥ 10	ASTM D-1000
180° peel adhesion (to stainless steel)	N/CM	≥ 1	ASTM D-1000
Tensile Strength	N/CM	≥ 12.8	ASTM D-1000
Elongation	%	130	ASTM D-1000

Characteristic: Good wear resistance, anti-erode, oil resistance and good adhesion

Applications: Better to protect pipe

Color: single color

Storage and transportation conditions:

- Tape should be stored in temperature 20°C-30°C, dry 50%-70% humidity area away from direct sunlight, air conditioner and other heat sources.
- Tape jumbos should be placed vertically with good package and avoid to be pressed against glue surface.
- Tape should be used within 12 months from the date of production.

Remarks: Surface that the tape is applied to should be clean, dry and free of grease, oil, moisture, dirt and other conditions.

Conforms to Rohs and Reach

Additions: The users should try first for small quantity,, and determine whether the product is suitable for his particular applications before large quantity.

Table Maker: Li Yang

Inspector: XU

Approval: Liu

Issued date: 2015-9-15

Edition:QR-JS

Address: No.1922 Room, Jiahong Building, No.658 Guangfulin Road, Songjiang District, Shanghai

Tel: +0086-21-6111 4575 Fax: 0086-21-6111 4576 Web: www.tiffanytape.com