



香港蒂梵尼膠帶有限公司

Hongkong Tiffany Tape Co.,Ltd

PE Foam Tape

一、 Product Introduction:

Backed with high performance PE foam, coated with solvent-acrylic glue, laminated with release liner, used in different fields widely with excellent performance.

二、 Product Features:

PE foam is made of closed-cell electronic cross-linked foam, excellent moisture resistance and water resistance

Good shock absorption, uniform foam cell structure, good resilience

Good at pasting in the rough surface, adhesive performance is good in a variety of surfaces, good noise reduction etc.

三、 Applications:

Electronics market: mobile phones, computers, digital cameras, machinery panels, membrane switches etc.;

Automotive market: the appearance of decorative articles, auto parts, car mark, car perfume etc.;

Home market: hooks, furniture, toys, handicrafts, window cracks, door crevices and other paste. Also used for silencers and shock absorption, electronic components packaging, glass plate surface pad solid and so on.

四、 Technique Data:

Item	Backing	Thickness (mm)	Valid Width(mm)	Release Liner	Color	Glue	Density (KG/m3)	Temperature (°C)
PE05125	IXPE	0.5	1050	Paper/Film	White/Black	acrylic	125	-20~110
PE08100	IXPE	0.8	1050	Paper/Film	White/Black	acrylic	100	-20~110
PE10100	IXPE	1	1050	Paper/Film	White/Black	acrylic	100	-20~110
PE1067	IXPE	1	1050	Paper/Film	White/Black	acrylic	67	-20~110
PE1050	IXPE	1	1050	Paper/Film	White/Black	acrylic	50	-20~110
PE1567	IXPE	1.5	1050	Paper/Film	White/Black	acrylic	67	-20~110
PE2067	IXPE	2	1050	Paper/Film	White/Black	acrylic	67	-20~110
PE3033	IXPE	3	1070	Paper/Film	White/Black	acrylic	33	-20~110

(If u need other thickness or density, please contact with our sales)

Address: No.1922 Room, Jiahong Building, No.658 Guangfulin Road, Songjiang District, Shanghai

Tel: +0086-21-6111 4575 Fax: 0086-21-6111 4576 Web: www.tiffanytape.com