



# 香港蒂梵尼胶带有限公司

## Hongkong Tiffany Tape Co.,Ltd

### PRODUCT DESCRIPTION

**TF-FTB04** Backed with PET film and reinforced with glass fiber.It's high strength and high performance

mono-directional filament tape;  
special adhesive left no residue after peeled off;suitable for fixing refrigerators;air-conditioners and electrical appliances industry.



**TF-FTB04**

### PERFORMANCE FEATURES

**TF-FTB04** is a transparent and high strength filament tape. Glass fiber contributes higher tensile strength and improved special synthetic rubber delivers stronger adhesion;good adhesion to the surface slightly stained by oil and without residue left;high resistance to abrasion;impact resistance and high holding power.

### STORAGE CONDITION

It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 4 to 26 °C and the humidity shall be between 40% and 50%.  
Rotate inventory recommended.

Physical Properties	Standard	Metric	Test Method	
Reinforcement	Fiberglass			
Adhesive	Synthetic Rubber and Resin			
Backing	PET			
Color	Clear			
Total Thickness	5.5mils	0.14mm	ASTM D-3652	GB/T7125
Peel Adhesion	58 oz/in	16N/25mm	ASTM D-3330	GB/T7122
Holding Power	≥48h	≥48h	ASTM D-3654	GB/T4851
Tensile strength	203 lbs/in	900N/25mm	ASTM D-3759	GB/T7753
Elongation at Break	5%	5%	ASTM D-3759	GB/T7753
Service Tem.--Mini	14°F	-10°C	BC/BD-220SE	BC/BD-220SE
Service Tem.--Max	176°F	80°C	DHG-9055A	DHG-9055A

\* Other dimensions available upon request

The above properties and results obtained refer to the average values of laboratory testing carried out on the samples of **TIFFANY** product. **TIFFANY** does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied. when used alone or in combination with other products. **TIFFANY** assumes no responsibility for any damage or injury sustained as a result of the use of its products.